SCHEDULE OF QUANTITIES

ABSTRACT - B

Name of work:- Improvement of Jarawa Ward i/c Construction of C.C & R.C.C. retaining walls, C.C. footpaths, Construction of 2 Nos. Toilet etc. for AAJVS at Kadamtala.

Sw. Construction of R.C.C. retaining wall.

| S.No Items of work Qty Rate Unit 1 Earth work in excavation over areas (exceeding 30cm in depth. 1.5m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto | Amount |
|--|--------------------|
| depth. 1.5m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto | ail I |
| disposal of excavated earth, lead upto 50m and lift upto | |
| | |
| | |
| 1.5m; disposed earth to be levelled and neatly dressed: | |
| a All kinds of soil 25.20 91.50 Cur | a 2305.80 |
| | |
| 2 Providing and laying in position cement concrete of | |
| specified grade excluding the cost of centring and | |
| shuttering - All work upto plinth level | d." |
| b 1:4:8 (1 Cement: 4 coarse sand: 8 graded stone aggregate 2.00 1404.70 Cur | n 2809.40 |
| 40 mm nominal size) | |
| A note that the property of th | |
| 3 Reinforcement for R.C.C. work including straightening, | |
| cutting, bending, placing in position and binding all | |
| complete . a Thermo-Mechanically Treated bars. 678.00 21.85 K | g 14814.30 |
| a Thermo-Mechanically Treated bars. | |
| 4 Providing and laying in position specified grade of | |
| reinforced cement concrete excluding the cost of centring, | |
| shuttering, finishing and reinforcement - All work upto | |
| plinth level | |
| a 1:2:4 (1 Cement: 2 coarse sand: 4 graded stone aggregate 7.00 1912.65 Cu | m 13388.5 |
| 20 mm nominal size) | |
| 5 Reinforced cement concrete work in walls (any thickness), | |
| | |
| including attached pilasters, buttresses, plinth and string | m 17182.4 |
| courses, fillets, columns, pillars, piers, abutments, posts 8.00 2147.80 Cu | ш 1/102.т |
| and struts, etc. upto floor five level excluding cost of | |
| centring, shuttering finishing and reinforcement. | |
| [18] - 18 - 19 - 19 - 19 - 19 - 19 - 19 - 19 | |
| 6 Centring and shuttering including strutting, propping etc. | |
| and removal of form for | |
| | ım 366.6 |
| concrete. b Walls (any thickness) including attached pilasters, 63,00 106,40 Sc | € 700 (|
| b Walls (any truckness) including attached phasers 63.00 106.40 50 butteresses, plinth and string courses etc. | įm 6703.2 |
| butteresses, pintal and sum courses out | |
| 7 Filling available excavated earth (excluding rock) in | |
| trenches, plinth, sides of foundations etc. in layers not | is in the city |
| exceeding 20cm in depth: consolidating each deposited 32.60 30.25 Co | ım 986. |
| layer by ramming and watering, lead up to 50 m and lift | |
| upto 1.5 m | |
| | |
| 8 12 mm cement plaster of mix: 1.4 (1 compant: 4 fine sand) 26.00 49.40 5 | gm 1284. |
| a 1:4 (1 cement : 4 fine sand) 26.00 49.40 5 | 1- |