S.No	Items of work	Qty	Rate	Unit	Amount
	oviding 40x5 mm flat iron hold fast 40 cm long		i i i i i i i i i i i i i i i i i i i	1811	
	including fixing to frame with 10 mm diameter bolts,				
44.4	nuts and wooden plugs and embeddings in cement	-0.00	06.00	T	0.07.50
	concrete block 30x10x15cm 1:3:6 mix (1cement : 3	10.00	36.75	Each	367.50
	coarse sand : 6 graded stone aggregate 20mm				
	nominal size)	4			
	tioning succy	2 / 5 / 5	F4 [
18	Providig and fixing MS grills of required pattern in		F		
	frames of windows etc with MS flat square or round			9	
	bars etc all complete.				
a	Fixed to openings/wooden frames with rowl plugs				
	screws etc.	20.00	37.90	Kg	758.00
	sciens etc.				
10	Cement concrete flooring 1:2:4 (1 Cement : 2 coarse				
17	sand: 4 graded stone aggregate) finished with a				
	floating coat of neat cement including cement slurry				et stommende
	but excluding the cost of nosing of steps etc				
41	complete.		710 50		1070 10
а	40mm thick with 20 mm nominal size stone	17.40	113.70	Sqm	1978.38
			200 E 100 E		
20	12mm thick cement plaster of mix				
a	1:4 (1 Cement : 4 fine sand)	76.00	49.40	Sqm	3754.40
		Tarining of Tarining of the Assault			
21	6mm thick cement plaster of mix:				
a	1:3 (1 Cement : 3 fine sand)	5.00	40.00	Sqm	200.00
22	12mm cement plaster finished with a floatig coat of				
1	neat cement of mix.				
a	1:3 (1 Cement : 3 fine sand)	8.30	67.55	Sqm	560.67
•	210 (2 0021011)				
23	White wahsing with lime to give an even shade.				
a	New work(three or more coats)	13.00	4.65	Sqm	60.45
23	Finishing walls with water proofing cement paint				
~	"Snowcem - Plus" of M/s Snowcem India Ltd., or	care for the			
	equivalent of required shade:			1111	
а	New work (Two or more coats applied @ 3.84 kg/10		00.77		900.90
u		39.00	23.10) Sqm	900.90
	sqm)			geljiller i t	
25	Distempering with oil bound washable distemper o				
25	approved brand and manufacture to give an ever				
	·				
886 _	shade New work (two or more coats) over and including				
а		16.00	29.7	0 Sqm	475.20
	priming coat with cement primer		J. 14		111.20
	* • . · · · · · · · · · · · · · · · ·				
26					
a	With ready mixed pink or grey primer of approved	38.00) 11 <i>.7</i>	5 Sqm	446.50
	brand and manufacture on wood work (hard and	1 38.00	, , , , , , , , , , , , , , , , , , , ,	Э	220.00
	soft wood)				
	. An allegar de la	•			
27	Painting with synthetic enamel paint of approved				
	brand and manufacture to give an even shade:	20 0	0 24.2	5 Cam	921.50
а	Two or more coats on new work	38.0	U 24.2	5 Sqm	921.00
	in the state of the same of the same of the same				0.0
21	3 Providing and fixing 4 mm thick plywood plai	n	A. J.		1 T
	lining with necessary screws, priming coat o	n			
	unexposed surface etc. complete with:				0444.00
ε	Teak ply facings of approved manufacture.	17.0	0 478.4	l0 Sqn	8132.80

ě