

S.No	Items of work	Qty	Rate	Unit	Amount
29	Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern with manually controlled device (handle lever) conforming to IS : 7231, Parryware/Hindware/Seabird/Orient (Coral) with all fittings and fixtures complete including cutting and making good the walls and floors wherever required.				
a	White Vitreous china Orissa pattern W.C. pan of size 580x440mm with integral type foot rests	2.00	1767.45	Each	3534.90
30	Providing and fixing plain bend of required degree.				
a	100 mm Sand cast iron S&S	2.00	120.70	Each	241.40
31	Providing and fixing heel rest sanitary bend				
a	100 mm dia Sand cast iron S&S	2.00	146.25	Each	292.50
32	Providing and fixing G.I pipes complete with G.I fittings and clamps, including cutting and making good the walls etc. (Internal work).				
a	15mm dia. Nominal bore	12.00	62.65	Mtr	751.80
33	Providing and fixing G.I pipes complete with G.I fittings including trenching and refilling etc. (external work).				
a	20mm dia. nominal bore	35.00	66.75	Mtr	2336.25
34	Providing and fixing brass stop cock of approved quality				
a	15 mm nominal bore	4.00	100.15	Each	400.60
b	20 mm nominal bore	1.00	121.15	Each	121.15
35	Providing and fixing brass bib cock of approved quality.				
a	15 mm nominal bore	2.00	100.15	Each	200.30
36	Making plinth protection 50mm thick of cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) over 75mm bed of dry brick ballast 40mm nominal size well rammed and consolidated and grouted with fine sand including finishing the top smooth.	30.00	131.20	Sqm	3936.00
37	Providing cements concrete surface drain with 1:4:8 (1 Cement : 4 sand : 8 graded stone aggregate 40mm nominal size) finished with 1:4 (1 Cement : 4 sand) including floating coat of neat cement earthwork in excavation and disposed or surplus earth etc.				
a	15cmx15cm surface drain.	70.00	437.00	Mtr	30590.00
38	Providing and fixing 1st quality ceramic glazed tiles conforming to IS 13753 of minimum thickness 5mm of approved make, colour shades except begundy, bottle green, black of any size as approved by engineer-in-charge in skirting, risers of steps and dados over 12mm thick bed of Cement Mortar 1:3 (1 Cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	12.00	373.30	Sqm	4479.60