	10	40									
	a management of the same of the same of				11	Beyond 120 cm girth upto and including 240 cm girth					
	•						each ;	2.000	1658.85	3317.70	
	k				id =	Above 240 cm girth	each .	2.000	3330.20	6660.40	No.
					11	Removing dead roofs				11	
							each	4.000	1769.75	7079.00	
					1	Beyond 120 cm girth upto and including 240 cm girth	- Lucii				
					la l	beyond 120 cm girth upto and including 240 cm girth	each	2.000	2500.00	5000.00	1
						the state of the s			3566.00	7132.00	
					11	Above 240 cm girth	each	2.000	3300.00	7132.00	The same of the sa
											2 2 22 22 22 22 22 22 22 22 22 22 22 22
						Excavation work in foundation trenches or drains not exceeding 1.5 m in width or 10 sqm on plan including dressing of sides and ramming of bottoms lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soils as directe					
						Ordinary rock	cum	43.050	185.42	7982.33	
						Supplying and filling of boulder into the back side retaining wall (30 cm width)	cum	18.900	2000.00	37800.00	
					1	aV				878630.38	
					++				1	878630.00	
					++						
		L			+-	(Rupees Eight Lakhs Seventy Eight Thousand Six Hundr	red Thir	ty Only)			
	The second secon					1 0 2 2					
					T	ABSTRACT :- "E"					
	eng x <sup>(d)</sup>				OTA	:- Construction of RCC Retaining wall of 03	eseta le	sight for a	Lougth 16	inte at Strait	V 9
1					SW	:- Construction of RCC Retaining wall of 05	mirn	eigni jor a	tengin 10	mu simi	
					Isla	nd					- A
		1		1 9		reement No. 28/A/EE/CD-I/PB/09-10					
	and the second of the second o	-				Excavation work in foundation trenches or drains not			1		
1					1	exceeding 1.5 m in width or 10 sum on plan including					
		8	S			dressing of sides and ramming of bottoms lift upto 1.5 m, including getting out the excavated soil and disposal	=		5		a = = =
						of surplus excavated soils as directed, within a lead of					
		1		ļ.		50m.	Cum	219.00	160.00	35040.00	
		-			11						
		-		-	-	Filling available excavated earth (excluding rock) in					
					11	trenches, plinth, sides of foundations etc. in layers not					
						exceeding 20cm in depth: consolidating each deposited					
		1 1				layer by ramming and watering, lead up to 50 m and lift	cum	71.80	120.00	8616.00	
					44	upto 1.5 m	Cum	71.00	120.00	0010.00	
					4				-		
					3	Providing and laying in position cement concrete of					
						specified grade excluding the cost of centring and			1		
				-		shuttering - All work upto plinth level					
						1:4:8 (1 Cement : 4 coarse sand : 8 graded stone					
						aggregate 40 mm nominal size)	Cum	5.40	12000.00	64800.00	
					11	Providing and laying in position specified grade of					
						reinforced cement concrete excluding the cost of					
					11	centring, shuttering, finishing and reinforcement - All					
						work upto plinth level					
					-	1:1.5:3 (1 Cement : 1.5 coarse sand : 3 graded stone	-		-		
						aggregate 20 mm nominal size)	cum	33.80	14500.00	490100.00	
		-		-	-	Phi chare to mill home to the					
					17	Reinforced cement concrete work in walls (any					
100	10 miles	× 10 - 10 - 10 10 1	1	4 99	11/	thickness), including attached pilasters, buttresses,			4 4 4 4 4	- Fag. 7	
			material Car	A Company of the Comp	-		-		5 of 500,00	and the latest the second	- Charles and the second of th
to certify a straining	The second secon		The state of the s	S. S		plinth and string courses, fillets, columns, pillars, piers,					
and the state of the state	the first that the state of the first	Bulancola posten	19.6(5)51 - Card	-		abutments, posts and struts, etc. upto floor five level		2 7 6	A A - 3	to don the second	THE PARTY OF THE P
10 E				44 Table 1991		excluding cost of centring, shuttering finishing and		1 2			
			. 7.11			reinforcement.	27-1	Contract of	1 3 - 5	Contract Contract of	and the second of the second o
	CONTRACTOR OF CO	5.55 E	1000	A company of the comp		I am a second and a second a second and a second a second and a second a second a second a second a second a second and a second a second a second a second a sec				VI	