

7	Centring and shuttering including strutting, propping etc. and removal of form for Foundations, footings, bases of columns etc. for mass concrete.					7	Centring and shuttering, including strutting, propping etc. and removal of form for								
a)	Columns, Pillars, Piers, Abutments, Posts and Struts	138.66	61.10	Sqm	8472.00	a)	Foundations footings, bases of columns etc. for mass concrete.	126.77	180.00	Sqm	22818.00				
b)	Lintels, beams, plinth beams, girders, bressumers and cantilevers.	28.80	135.80	Sqm	3911.00	b)	Columns, Pillars, Piers, Abutments, Posts and Struts	27.36	200.00	Sqm	5472.00				
c)	Suspended floors, roofs, landings, balconies and access platform.	26.40	87.95	Sqm	2322.00	c)	Lintels, beams, plinth beams, girders, bressumers and cantilevers.	25.54	225.00	Sqm	5747.00				
d)	Extra for shuttering in circular work (20% of respective centring and shuttering items)	12.60	111.20	Sqm	1401.00	d)	Suspended floors, roofs, landings, balconies and access platform.	11.52	250.00	Sqm	2880.00				
8	Supplying and stacking of graded stone aggregate at site of size range	27.73	12.22	Sqm	339.00	8	Extra for shuttering in circular work (20% of respective centring and shuttering items)	103.83	200.00	Sqm	20766.00				
9	90 mm to 45 mm					9	Supplying and stacking of graded stone aggregate at site of size range								
a)	Providing hollow cement concrete block walling, upto floor five level 200 mm thick consisting of using hollow block of size 400 mm x 200 mm x 200 mm of mix 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate of 10 mm nominal size) laid in cement mortar 1:6 (1 cement : 3 coarse sand)	13.06	3802.00	cum	49662.00	a)	90 mm to 45 mm	7.67	3000.00	cum	23010.00				
10						10	Providing hollow cement concrete block walling upto floor five level 200 mm thick consisting of using hollow block of size 400 mm x 200 mm x 200 mm of mix 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate of 10 mm nominal size) laid in cement mortar 1:6 (1 cement : 3 coarse sand)								
	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows including ISI marked black enamelled M.S butt hinges with necessary screws excluding, panelling which will be paid for separately.	4.00	5081.60	cum	20326.00			5.17	3000.00	cum	41384.00				
11	Second class teak wood					11	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows including ISI marked black enamelled M.S butt hinges with necessary screws excluding, panelling which will be paid								
a)	35 mm thick shutters	2.50	1047.65	Sqm	2619.00	a)	Second class teak wood								
b)	Providing wood work in frames of doors, windows clerestory windows and other frames, wrought framed and fixed in position.					b)	35 mm thick shutters	2.31	2000.00	Sqm	4620.00				
12						12	Providing wood work in frames of doors, windows clerestory windows and other frames, wrought framed and fixed in position.								
a)	Second class superior hard wood category -II	0.10	33150.00	cum	3315.00	a)	Second class superior hard wood category -II	0.075	30000.00	cum	2250.00				
13	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. all complete.					13	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. all complete.								
a)	Fixed to openings / wooden frames with rawl plugs (designation 10 No.) etc., all complete	15.00	37.90	kg	569.00	a)	Fixed to openings / wooden frames with rawl plugs (designation 10 No.) etc., all complete	20.00	30.00	kg	1600.00				
14	Making plinth protection 50mm thick of cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) over 75mm bed of dry brick ballast 40mm nominal size well rammed and consolidated and grouted with fine sand including finishing the top smooth.	25.62	131.20	Sqm	3361.00	14	Making plinth protection 50mm thick of cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) over 75mm bed of dry brick ballast 40mm nominal size well rammed and consolidated and grouted with fine sand including finishing the top smooth.	31.36	700.00	Sqm	21952.00				
	Providing cement concrete surface drain i/c earth work 10 cm thick base concrete and 15 mm thick side wall with 1:4:8 and cement concrete finished with 1:4 i/c floating coat of neat cement inside the drain i/c disposal of surplus earth work complete.					15	Providing cement concrete surface drain i/c earth work 10 cm thick base concrete and 15 mm thick side wall with 1:4:8 and cement concrete finished with 1:4 i/c floating coat of neat cement inside the drain i/c disposal of surplus earth work complete.								