

|  |  |  |  |  |    |   |     |         |         |            |       |      |         |          |  |
|--|--|--|--|--|----|---|-----|---------|---------|------------|-------|------|---------|----------|--|
|  |  |  |  |  | 36 | Providing and fixing 1st quality ceramic glazed tiles conforming to IS : 13753 of minimum thickness 5 mm of approved make like NITCO, ORIENT, SOMANY KAJARIA, or equivalent make in all colours, shades except begundy, bottle green, black of any size as approved by Enineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of Cement Mortar 1:3 (1 Cement : 3                               | Sqm | 279.28  | 1550.00 | 432884.00  | 27.90 | Sqm  | 1550.00 | 43245.00 |  |
|  |  |  |  |  | 37 | Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 13755 of NITCO, ORIENT, SOMANY KAJARIA, or equivalent make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick Cement Mortar 1:4 (1 Cement : 4 Coarse sand) including pointing, the joints with white cement and matching pigment etc., complete. | Sqm | 349.00  | 1800.00 | 628200.00  | 34.90 | Sqm  | 1800.00 | 62820.00 |  |
|  |  |  |  |  | 38 | Providing corrugated G.S. sheet roofing fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead and including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (upto a pitch of 60 degrees) excluding the cost of purlins, rafters and trusses.                 |     |         |         |            |       |      |         |          |  |
|  |  |  |  |  | a) | 0.80mm thick with zinc coating not less than 275gm/m <sup>2</sup>   | Sqm | 1065.15 | 1900.00 | 2023785.00 | 0.00  | 0.00 | 0.00    | 0.00     |  |

158