

32	Providing and fixing wash basin with C.I./M.S. brackets, 15 mm C.P. brass pillar taps, Kingston/Gem/Techno/Parko, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require :A] White Vitreous china					32	Providing and fixing wash basin with C.I./M.S. brackets, 15 mm C.P. brass pillar taps, Kingston/Gem/Techno/Parko, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require :A] White Vitreous china				
a)	Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps	2.00	1064.05	each	2128.10	a)	Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps	2.00	2850.00	each	5700.00
33	Providing and fixing G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc. (internal work)					33	Providing and fixing G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc. (internal work)				
a)	Exposed on wall					a)	Exposed on wall				
b)	15mm dia. nominal bore	11.20	62.65	metre	701.68	b)	15mm dia. nominal bore	36.00	250.00	metre	9000.00
b)	20mm dia. nominal bore	15.00	78.65	metre	1179.75	c)	20mm dia. nominal bore	35.00	325.00	metre	11375.00
34	Providing and fixing brass bib cock of approved quality.					34	Providing and fixing brass bib cock of approved quality.				
a)	15 mm nominal bore	3.00	100.15	each	300.45	a)	15 mm nominal bore	5.00	275.00	each	1375.00
35	Providing and fixing brass stop cock of approved quality					35	Providing and fixing brass stop cock of approved quality				
a)	15 mm nominal bore	3.00	100.15	each	300.45	a)	15 mm nominal bore	3.00	265.00	each	795.00
36	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end)					36	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end)				
a)	40 mm nominal bore	1.00	287.35	each	287.35	a)	40 mm nominal bore	0.00	0.00	each	0.00
37	Providing and fixing G.I. pipes complete with G.I. fittings including trenching and refilling etc. (external work)					37	Providing and fixing G.I. pipes complete with G.I. fittings including trenching and refilling etc. (external work)				
a)	40mm dia. nominal bore	31.00	116.50	metre	3611.50	a)	40mm dia. nominal bore	0.00	0.00	metre	0.00
38	Providing and laying hollow cement concrete block walling upto floor level 200mm thick consisting of hollow block of size 400mm x 200mm x 200mm of mix 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 10mm nominal size) having a crushing strength of 3.5N/Sqmm at 28 days as per IS:2185 (Part-I) 1979 laid in cement mortar 1:6 (1 cement 6 coarse sand) upto floor five level.	16.00	2750.00	cum	44000.00	38	Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI : 12701 marked indicating the BIS License No. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank [Sintex, Electroplast, Star, Lotus or equivalent having valid ISI license].	2000.00	10.50	per litre capacity	21000.00
39	Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI : 12701 marked indicating the BIS License No. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank [Sintex, Electroplast, Star, Lotus or equivalent having valid ISI license].	2000.00	3.95	per litre capacity	7900.00	39	Constructing brick masonry manhole in cement mortar 1:4 (1 cement : 4 coarse sand) R.C.C. top slab with 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 mix (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size) finished with a floating coat of neat cement complete as per standard design.				