											(a)
					52	Structural steel work in single section fixed without connecting plate including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all					
					53	complete.	2500.00	77.05	kilogram	192625.00	
		8			55	Providing and fixing M.S. fan clamp type I of 16 mm dia M.S. bar bent to shape with hooked ends in R.C.C. slabs during laying including painting the exposed portion of	204.06	82.0			· · · · · · · · · · · · · · · · · · ·
					54	loop, all as per standard design complete. Providing and fixing bolts upto 300 mm in	204,06	83.2	each	16977.79	
				il il	55	length including nuts and washers Painting with black anti-corrosive	156.00	96.15	kilogram	14999.40	
4						bitumastic paint of approved brand and manufacture to give an even shade:				^	
1					a)	Two or more coats on new work.	322.59	39.05	sqm	12597.22	
		= "			56	Steel work welded in built up- sections/framed work including cutting hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc.as required.	5 5 2				
-					a)	In gratings, frames, guard bar, ladders, railings, brackets, gates & similar works.	2580.08	118	kilogram	304449.44	
					57	Applying one coat of cement primer of approved brand and manufacture on wall surface :		¥			
					a)	Cement primer	842.53	34.05	CON	20/00 15	
					58	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete.	042.33	34,03	sqm	28688.15	
+	(C) (C)					Semi rigid pipe					
+						32 mm dia	3	117.45	each	352.35	
						Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing.					
			-			Rectangular shape 453x357mm	2	1738,6	each	3477.20	
+				- 1		Providing and fixing soil, waste and vent pipes: 100 mm dia.					
			-			Sand cast iron S&S pipe as per IS: 1729.	107	700 55			
						75 mm diameter :	17	733.55	metre	12470.35	
-					d)	Sand cast iron S&S pipe as per IS: 1729.	11	634.45	metre	6978.95	
					61	Providing and fixing bend of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete.			Hette	0770.93	
					a)	100 mm					
+					b)	Sand cast iron S&S as per IS - 1729	4	620.3	each	2481.20	
			-			75 mm dia					
						Sand cast iron S&S as per IS - 1729 Providing and fixing terminal guard:	6	420.7	each	2524.20	
+					a)	100 mm					
					b)	Sand cast iron S&S as per IS - 1729	1	258.05	each	258.05	