			Providing and fixing factory made P.V.C. door frame manufactured by M/s Rajshri or equivalent of size 50x47mm with a wall thickness of 5mm, made out of extruded 5mm rigid PVC foam sheet mitred at corners and joined with 2 Nos. of 150mm long brackets of 15x15mm M.S. square tube, the vertical door profiles to be reinforced with 19x19mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S. screws of 65/100mm size complete as per manufacturers speci fication and direction of Engineer-in-Charge.	Metre 93.67	370.00 34657	90
	Sec.		58 Providing and fixing 30mm thick factory made PVC rigid foam panelled door shutters manufactured by M/s. Rajshri or equivalent made from M.S. tube of 19x19mm. 19 gauge for styles and 15x15mm for top and bottom rails, covered with heat moulded prelaminated PVC "C' channel of 5mm thick sheet and 30x50mm wide to form styles and 5mm thick and 75mm wide prelaminated PVC sheets for top rail, lock rail and bottom rail on either side and 5mm thick, 20mm wide cross PVC sheet as gap insert for top rail and bottom rail, panelling of 5mm	Sqm 27.74	3000.00 8321	7.00
· (Agament)		1	thick PVC sheet prelaminiated on both sides fitted in the M.S. frame welded/sealed to the styles and rails with 5x30mm prelaminated PVC sheet beading on either side and joined together with solvent cement adhesive etc., complete as per manufacturers specification and direction of Engineer-in-Charge fixed to frames with 4 Nos. M.S. powder coated butt hinges (For Internal Shuttgreat).			