

			93	Providing and fixing level adjusting hangers of 6 mm dia. M.S. rods (upto 1200mm length) fixed to roof slabs by means of M.S. angle ceiling cleats 40x40x5mm size 40mm long and expansion hold fastners 12.5 mm dia. 40mm long including applying priming coat of zinc chromate yellow primer for steel members complete				0.00	
			94	Providing and laying water proofing treatment to vertical and horizontal surfaces of depressed portions of W.C., kitchen and the like consisting of : (i) 1st course of applying cement slurry @ 4.4 Kg/sqm mixed with water proofing compound 'Impermo' of Snowcem or equivalent conforming to IS 2645 in recommended proportions. (ii) 1st course of 20mm cement plaster 1:3 (1 cement : 3 coarse sand) mixed with water proofing compound in recommended proportion. (iii) 1st course of applying blown or residual				0.00	
								11564574.10	
							Rebate @ 4 %	462582.96	
								11101991.00	
			95	Removing of dead roots upto 1.50 m height above the ground level including excavating earth and removing roots brass ground disposal of drubbish lead upto 50 mm and lift upto 1.50					
			a)	Beyond 30 cm girth upto and including 60 cm girth	Nos	25.00	132.00	3300.00	
			b)	Beyond 60 cm girth upto and including 120 cm girth	Nos	15.00	264.00	3960.00	
			c)	Beyond 120cm girth upto and including 240 cm girth	Nos	131.00	990.00	129690.00	
			d)	Above 240 cm girth	Nos	26.00	1584.00	41184.00	
			96	Clearing jungle including uprooting of rank vegetation, grass, brush wood, trees and saplings of girth upto 30 cm measured at a height of 1 m above ground level and removal of drubbish	100/Sqm	5600.00	335.95	18813.20	