

|  |  |  |  |     |  |       |         |         |          |  |  |
|--|--|--|--|-----|--|-------|---------|---------|----------|--|--|
|  |  |  |  | 97  | Carriage of Pulverised sand from Brookshadabad quarry to Phoneix Bay Jetty i/c loading at Jetty by Mechanical Transport for an average lead of 12 km loading the same into ship and unloading at Straight Island Jetty.  | Cum   | 42.56   | 1404.74 | 59785.73 |  |  |
|  |  |  |  | 98  | Carriage of Tor steel from Dispatch sanction of CD-L Port Blair to Phoneix Bay jetty by Mechanical Transport for an average lead 1 km and loading the same into ship and unloading at Straight Island Jetty.   | Tonne | 3.97    | 1375.90 | 5462.32  |  |  |
|  |  |  |  | 99  | Felling trees of the girth (measured at a height of 1 m above ground level) including cutting of trunks and branches removing the roots and <del>including of removable material and</del> Beyond 60 cm girth upto and including 120 cm girth  | No    | 1.00    | 388.50  | 388.50   |  |  |
|  |  |  |  | 100 | Removing of dead roots upto 1.50 m height above the ground level including excavating earth and removing roots brass groud desposal of drubbish lead upto 50 mm and lift upto 1.50   |       |         |         |          |  |  |
|  |  |  |  | a)  | Beyond 120cm girth upto and including 240 cm girth   | Nos   | 12.00   | 1769.75 | 21237.00 |  |  |
|  |  |  |  | b)  | Above 240 cm girth   | Nos   | 1.00    | 3566.00 | 3566.00  |  |  |
|  |  |  |  | 101 | Applying one coat of cement primer of approved brand and manufacture on wall surface :   |       |         |         |          |  |  |
|  |  |  |  | a   | Cement primer.   | Sqm   | 1113.97 | 31.00   | 34533.19 |  |  |
|  |  |  |  | 102 | Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth upto 1.5 m including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth including consolidating each deposited layer by ramming, watering, etc. and |       |         |         |          |  |  |
|  |  |  |  | a   | All kinds of soil  |       |         |         |          |  |  |
|  |  |  |  | b)  | Pipes, cables etc, not exceeding 80 mm dia.  | Metre | 165.53  | 105.05  | 17388.93 |  |  |
|  |  |  |  | 103 | Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931  |       |         |         |          |  |  |