8.						
, 15	MR	Providing and fixing 35mm thick panelled, glazed or panelled & glazed shutters for door	, ,			3
		including MS Butt hinges with necessary screws with superior hard wood including panelling				
		with 12mm thick marine ply (BWR) conforming to relevant specification complete with wooden			4	
		cleats & blocks as directed by Engineer in charge.		<u>.</u>		
a		Superior hard wood Cat-II (Kiln seasoned & chemically treated)	2.1	Sgm -	2045.70	4295.97
16	9.53	Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm	*			
		diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15cm			1. 11	
		1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size)	8	Each	. 61.5	492
17	9.96	Providing and fixing aluminium sliding door bolts ISI marked anodised (anodic coating not less				
		than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with nuts				
	İ	and screws etc. complete :	. 4.			
/ a	9.96.1	300x16 mm	2	Each	158.5	317
18	9.97	Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than				
		grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with necessary			,	
ŀ		screws etc. complete :	Service on the service			
a	9.97.2	250x10 mm	1	Each	52.2	62.2
19	9.100	Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than				
		grade AC 10 as per IŞ : 1868) transparent or dyed to required colour or shade with necessary				
		screws etc. complete :	•			
â	9.100.1	125 mm	2	Each	48.8	97.6
20	11.3	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished		2		
		with a floating coat of neat cement including cement slurry, but excluding the cost of nosing of				
	2	steps etc. complete.				
	11.3.1	40mm thick with 20mm nominal size stone aggregate.	4	Sqm	192.95	771.8
21	13.1	12 mm cement plaster of mix :				
а	13.1.1	1:4 (1 cement : 4 fine sand)	46.2	Sqm	77.55	3582.81
22	14.45	Distempering with oil bound washable distemper of approved brand and manufacture to give				
ija .		an even shade :	The state of the s	â		
a a	14.45.1	Old work (one or more coats)	14.1	Sqm	14.9	210.09
23	14.54	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:			William III	
9	14.54.1	One or more coats on old work.	4.9	Sgm	22.85	111.965