100	6						
- [	24	17.1	Providing and fixing water closet squatting pan (Indian type W.C. pan ) with 100mm sand cast				
			Iron P or S trap, 10 litre low level white P.V.C. flushing cistern with manually controlled device				***
			(handle lever) conforming to IS: 7231, with all fittings and fixtures complete including cutting				
			and making good the walls and floors wherever required:		The state of the s		
-	ā	17.1.1	White Vitreous china Orissa pattern W.C. pan of size 580x440mm with integral type foot rests.				
		17.1.1	White victods almo orisse partern with part of size sook realm with sitegral type foot tests.	2	Each	2304.65	4609.3
	25	17.7	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps,32 mm C.P.				:::
ļ			brass waste of standard pattern, including painting of fittings and brackets, cutting and				
			making good the walls wherever require :				
Г	a	17.7.2	White Vitreous China Wash basin size 630x450 mm with a single 15 mm C.P. brass pillar tap.	To			
				1	Each	1201.7	1201.7
	26	18.15	Providing and fixing brass bib cock of approved quality:		·		
1	ā	18.15.1	15 mm nominal bore	3	Each	191.7	575.1
	27	17:31	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality)				
			complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws	4			
上			and washers-complete.	2	Each	493.65	987.3
	28	18.10	Providing and fixing G.I. pipes complete with G.I. fittings and clamps, including cutting and				
			making good the walls etc.	# <b>"</b>			
			Internal work - Exposed on wall				
	а	18.10.1	15 mm dia. nominal bore	18	. Metre	105.85	1905.3
L	ъ	18.10.3	25 mm dia. nominal bore	24	Metre	179.65	4311.8
	29	18.12	Providing and fixing G.I. pipes complete with G.I. fittings including trenching and refilling etc.				
	*1		·				-
_			External work :				
		18.12.5	40 mm dia. nominal bore	. 18	Metre	219.6	3952.8
	30	18.13	Making connection of G.I. distribution branch with G.I. main of following sizes by providing and				
			fixing tee, including cutting and threading the pipe etc. complete:		ļ.		
1		18.13.1	25 to 40 mm nominal bore	2	Each	166.05	332.1
Ê	31	18.16	Providing and fixing brass stop cock of approved quality:				
	а	18.16.1	15 mm nominal bore	8	Each	191.7	1533.6
	32	14.42	White washing with lime to give an even shade :		- 1		
		14.42.1	Old work (two or more coats)	4	Sqm	4.1	15.4