

7	5.2	Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. upto floor five level excluding cost of centring, shuttering, finishing and reinforcement.								
	5.2.2	1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20 mm nominal size)								
		Plinth Beam	1	4	2	0.3	0.3	0.72		
		column	1	4	0.3	0.3	3	1.08		
		Tie Beam	1	4	2	0.3	0.3	0.72		
		slab	1	1	2.3	2.3	0.15	0.79		
								3.3		
							Say	3.3	Cum	
8	5.9	Centring and shuttering including strutting, propping etc. and removal of form for :								
	5.9.1	Foundations, footings, bases of columns, etc. for mass concrete.								
		footing	1	4	4	1.2	0.2	3.84		
		Pedestal	1	4	4	0.6	0.15	1.44		
		Plinth Wall	2	4	2		0.45	7.20		
		s/column	1	4	4	0.3	0.55	2.64		
								15.1		
							Say	15.0	Sqm	
	5.9.3	Suspended floors, roofs, landings, balconies and access platform.								
			1	2	2.3	2.3		10.58		
								10.6		
							Say	11.0	Sqm	
	5.9.5	Lintels, beams, plinth beams, girders, bressumers and cantilevers.								
		Plinth Beam	1	4	2	2	0.3	4.80		
		Tie Beam	1	4	3	2	0.3	7.20		
								12.0		
							Say	12.0	Sqm	
	5.9.6	Columns, Pillars, Piers, Abutments, Posts and Struts.								
			1	4	4	0.3	3	14.40		
								14.4		
							Say	14.0	Sqm	
9	5.22	Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete.								
	5.22.3	Cold twisted bars								
		Footing	1	4	16	1.2	0.89	68.35		
		Plinth Beam/ Tie Beam	2	4	6	2.9	1.58	219.94		
		columns-16mm	1	4	6	5.3	1.6	203.52		
		stirrups-8mm	1	4	36	0.9	0.4	51.84		
		slab-10mm	1	2	16	2.3	0.62	45.63		
			1	2	16	2.3	0.62	45.63		
								634.9		
							Say	635.0	Kgs	
10	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sum including pointing in white cement mixed with pigment of matching shade complete.								
		Walling	1	1	2	2	3.75	15.00		
			1	1	2	2	3.7	14.80		
								29.8		
							Say	30.0	Sqm	