

11	11.37	Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick Cement Mortar 1:4 (1 Cement : 4 Coarse sand) including pointing the joints with white cement and matching pigment etc., complete.									
		Flooring	1	2	3.75	3.7				27.75	
										27.8	
12	12.8	Providing non-asbestos high impact Polypropylene reinforced cement 6 mm thick corrugated sheets (As per IS:14871) roofing upto any pitch and fixing with polymer coated J or L hooks, bolts and nuts 8mm dia. G.I. plain and bitumen washers or with self drilling fastener and EPDM washers etc. complete excluding the cost of purlins, rafters and trusses: corrugated sheets and including cutting to size and shape wherever required.							Say	28.0	Sqm
			1	1	3				2.5	7.5	
										7.5	
13	MR	Providing wood work in frames of doors, windows, clerestory windows and other frames wrought framed and fixed in position with:							Say	8.0	Sqm
	a	Superior hard wood Cat-II (Kiln seasoned & chemically treated)									
		D1	1	1	0.9	0.1	0.08			0.01	
			1	2	2.1	0.1	0.08			0.03	
		W1	1	2	1.2	0.1	0.08			0.02	
			1	2	1.2	0.1	0.08			0.02	
										0.1	
14	MR	Providing and laying hollow cement concrete blocks walling 200mm thick consisting of hollow block size 400X200X200mm of mix 1:3:6(1 cement 3 coarse sand 6 graded stone aggregate 10mm nominal and down size) laid in cement mortar 1:6(1 cement 6 coarse sand). a) Up to floor five level.							Say	0.1	Cum
		HB Wall	1	4	2	0.2	2			3.20	
		D1	1	1	1.2	0.2	2			-0.48	
										2.7	
15	MR	Providing and fixing 35mm thick panelled, glazed or panelled & glazed shutters for door including MS Butt hinges with necessary screws with superior hard wood including panelling with 12mm thick marine ply (BWR) conforming to relevant specification complete with wooden cleats & blocks as directed by Engineer in charge.							Say	2.7	Sqm
	a	Superior hard wood Cat-II (Kiln seasoned & chemically treated)									
		D1	1		1		2.1			2.1	
										2.1	
16	9.53	Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size)							Say	2.1	Sqm
		D1	2				4			8	
										8.0	
17	9.96	Providing and fixing aluminium sliding door bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with nuts and screws etc. complete :							Say	8.0	Each
a	9.96.1	300x16 mm									
		DOOR-D1	1				2			2	
										2.0	