	Γ .				T .	T*****		Say	2.0	Each
8 .	9.97	Providing and fixing aluminium tower bolts ISI mark	ed anodised							
,		(anodic coating not less than grade AC 10 as per					1			
٠		transparent or dyed to required colour or shade with								
	İ	screws etc. complete :	in Accessiny							
	9.97.2	250x10 mm		··· ••••••••••••••••••••••••••••••••••	<u> </u>	<del> </del>			-	-
		DOOR-D1		1	<del> </del>	-		1.	1	+
			0001102		<del></del>			<i></i>	1.0	·
	<del>}</del>			*******				Say	1.0	Each
19	9 100	Providing and fixing aluminium handles ISI marked anod	lisad (anadic			<del> </del>		Зау	1.0	Laci
	100	coating not less than grade AC 10 as per IS: 1868) transparent or								
		dved to required colour or shade with necessary screws etc. complete								
	9.100.1	125 mm								
	9.100.1									-
	ļ	DOOR-D1		1		ļ		2	2	<del> </del>
	ļ								2.0	
								Say	2.0	Each
200	7773	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded					-			
	1	stone aggregate) finished with a floating coat of neat cement								
		including cement slurry, but excluding the cost of nosing	of steps etc.	,						
		complete.								
	11.3.1	40mm thick with 20mm nominal size stone aggregate.								
			-	1	1	2.	2		4.00	
									4.0	
								Say	4.0	Sqm
1.	13.1	12 mm cement plaster of mix :		·						1
а	13.1.1	1:4 (1 cement : 4 fine sand)								
			HB Wall	2	2	2	2		16.00	+
	<b> </b>			2	2	2	2		16.00	
		staging column			4	0.3	3		3.60	
						<del> </del>				
			slab	1	- 2	2.3	2.3		10.58	
				·		ļ			46.2	-
22	14.45	Distribution with all hand and the 12's			ļ		ļ	Say	46.2	Sqm
	£41.44_1	Distempering with oil bound washable distemper of app and manufacture to give an even shade:	roved brand							
1 2	14.45 1	Old work (one or more coats)			ļ					
175.	14,45 1	Oid work (one of more coats)								
	ļ		HB Wall	1	2	2	2		8.00	
	ļ			1:	,2	2	2		8.00	
			D1	1	1	0.9	2.1		-1.89	
									14.1	
								Say	14.1	Sam
23	14.54	Painting with synthetic enamel paint of approved	brand and							
		manufacture of required colour to give an even shade :		:		İ				
	14.54.1	One or more coats on old work.								
		W 122 days (1994)	-0							
			D1	1	2	0.9	2.1	2.6	4.914	1
									4.9	┪
					<u> </u>			Say	4.9	Sqm
4	17.1	Providing and fixing water closet squatting pan (Indian type	e W.C. pan 1						7.3	Sqin
		with 100mm sand cast Iron P or S trap, 10 litre low level	white P.V.C.							
		flushing cistern with manually controlled device (h	andle lever)							
		conforming to IS: 7231, with all fittings and fixtures complete								
		including cutting and making good the walls and floors wherever								1
mar:		required :						ļ., l		
ล	17 1.1	White Vitreous china Orissa pattern W.C. pan of size 580x440mm			<del>  </del>	ļi				
	L	with integral type foot rests.	- 30/17/04/1111				. !			
	<del> </del>			1	-		<del></del>			
		Maria Maria		-1	2				2	-
		The state of the s		- 1			. I		2.0	
		The state of the s						Say.	2.0	