5	17,7	Previding and fixing wash basin with C.I. brackets, 15 mm C.P. brass							
		pillar taps,32 mm C.P. brass waste of standard pattern, including							
u <sub>t</sub>		painting of fittings and brackets; cutting and making good the walls						ii.	
-		wherever require :		٠.		÷			
	17.7.2	White Vitreous China Wash basin size 630x450 mm with a single 15							
		mm C.P. brass pillar tap.							0
<del></del> -		THE CALL STREET COLOR	1	1				1	-
								1.0	<del> </del>
							C		Ench
							Say	1.0	Each
5	18.15	Providing and fixing brass bib cock of approved quality:							
	18.15.1	15 mm Bominal bore							ļ <u>.</u>
			l	3				3	
								3.0	
							Say	3.0	Each
7	17.31	Providing and fixing 600x450 mm beveled edge mirror of superior							
		glass (of approved quality) complete with 6 mm thick hard board							
		ground fixed to wooden cleats with C.P. brass screws and washers			1				
A		complete.							
-		complete.	1	2				2	-
					-				
		•			<del> </del>			2.0	
					ļ		Say	2.0	Each
3	18.10	Providing and fixing G.I. pipes complete with G.I. fittings and clamps,			1				
		including cutting and making good the walls etc.							
		Internal work - Exposed on wall						,	
	18.10.1	15 mm dia. nominal bore							
*****			1	3	6			18	1
								18.0	-
					<del> </del>	<del> </del>	F		00.00
	10.10.2	26		-	<del> </del>		Say	18.0	Metr
	18.10.5	25 mm dia, nominal bore		ļ					
					ļ				
,			1	4	6			24	
								24.0	
							Say	24.0	Metr
9	18.12	Providing and fixing G.I. pipes complete with G.I. fittings including			-		· · · · · · · · · · · · · · · · · · ·		~
		trenching and refilling etc.		1					
		External work :		1					
72	18.12.5	40 mm dia. nominal bore		<del> </del>				<del> </del>	
range.				- 41					
					-			ļ	
			1	3	6		ļ	1.8	
								18.0	
							Say	18.0	Metr
0	18.13	Making connection of G.I. distribution branch with G.I. main of							
		following sizes by providing and fixing tee, including cutting and							
		threading the pipe etc. complete :			1		1		
	18.13.1	25 to 40 mm nominal bore				<b> </b>			
		3000	11						
-			1	1	2	<del> </del>		-	
			-	1	-	<del> </del>		2	
				ļ	-	-		2.0	
1	18.16	Providing and fixing brass stop cock of approved quality	<del> </del>			<u> </u>	Say	2.0	Each
			ļ						
	18.16.1	15 mm nominal bore							
	<del> </del>		4	2				8	
								8.0	-
					<del></del>		Say	8.0	Éach
2	14.42	White washing with lime to give an even shade:	<del>                                     </del>		-		Jay	·	cacn
	14.42.1				+			ļ	
		4				1	1.		
	1		ļ		1				
Ú.	<del> </del>		1	1	2	2		4.00	
de la constant								4.0	
de la	-					7	<del> </del>		
							Sav	4.0	Sam
3	13.62	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:					Say	4.0	Sqm