Chisel :-

The implement comprises of a shaft, measuring about 90 cm to a mtr., fastened to an iron blade, about 15 cm in length, 1 cm in thi7ckness and 4.5 c, in breadth. The sharp cutting edge of the blade is slightly broader than its butt.

Dug out wooden bucket :-

the handle while carrying honey.

The wooden bucket called he 'ookoo' may be as big as 40 cm in diameter and 60 cm in length. But the common size of an ookoo varies from 30 to 40 cm in length and 20 to 25 cm in dia neter. A log of a suitable size of soft and light wood is selected for the bucket. First, a small cavity is made right at the centre of the surface selected for the mouth of the bucket. The wooden chips are first taken out carefully with the help of an adze till the cavity becomes big enough for use of the chisel. With the chise the craftsman goes on slowly chiseling out of wooden chips from the centre towards the periphery of the log. While doing so he holds the log either between the thighs with the base on the ground. The 'digging' is simultaneous done horizontally as well as longititudinally, in a circular fashion, so that the log gets hollowed out in depth and breadth. The next phase of digging starts from the place where the previous phase had ended, following the same direction, the peripheral wall is reduced to about 0.5 cm. The thickness at the bottom of the busket remains slightly more than that of the wall. A thin layer of wax is applied all over the inner surface. This is done by putting pieces of wax inside and rotating the bucket against a fire. The coating of wax makes the insides of the bucket smooth and at the same time helps fill up the small cracks that may have appeared on the body of the bucket. Two strips of bark are tied around the outer surface of the bucket, one a few inches below the upper rim and the other a few inc es above the rim of the base. Both the rings of bark strip are joined longitudinally at several places, at a distance of a few inches from one another. This is done all over the outer wall of the basket. The ring of bark strip above the base is jo ed transversely by bark strips at two or four points by passing them under the pottom of the basket firmly. The two ends of a long strip of bark are tied to the ing of bark strip near the upper rim to serve as