

B/E- 425074/00

f)	Extra for every 0.30 m additional height of floor above named normal height of 2.9 m $3.60 - 2.90 = 0.70$ m $\frac{17}{0.3} \times 0.70 = 39.17/$ Sqm.	194.16	Sqm.	39.57	Sqm.	7583/00
g)	Construction height of F.F. portion having an average height of 3.00 m (first floor)	317.73	Sqm.	375.00	Sqm.	119149/00
h)	Extra for additional height $3 - 2.90 = 0.10$ m $\frac{17}{0.3} \times 0.10 = 5.67/$ Sqm.	317.73	Sqm.	5.67	Sqm.	1802/00
2)	Extra for foundation in poor soil having bearing capacity less than 10T/ Sqm.	3x509.69	Sqm.	15.00	Sqm.	22936/00
3)	Resisting earthquake forces.	3x509.69	Sqm.	34.00	Sqm.	51988/00
4)	Termite proof treatment (on G.Fonly)	309.69	Sqm.	9.00	Sqm.	4587/00
5)	Internal water supply and sanitary installations M. 576544/-			15.00	100	36432/00
6)	Internal electrical installations M. 57	576544/-		12.30	100	72068/00
7)	External service connections.	576544/-		5.00	100	28327/00

G/O- 520496/00